

SADATRAY CY UL LISTED

MTW TC-ER CIC TRAY CABLE - EXPOSED RUN



MADE IN ITALY

SCHEMATO/SHEILED

ADATTO PER LA POSA INTERRATA DIRETTA | DIRECT BURIAL



CARATTERISTICHE TECNICHE

TECHNICAL FEATURES



CONDUTTORE
CONDUCTOR

Rame flessibile Cl.5 acc. CEI 20-29 DIN VDE 0295 e IEC 60228, UL 83 standard
Flexible bare copper conductor Cl.5 acc. CEI 20-29 DIN-VDE 0295 and IEC60228, UL 83 standard



TENSIONE NOMINALE
NOMINAL VOLTAGE

600 V UL
IEC 300/500 V



ISOLAMENTO
INSULATION

Miscela speciale di PVC Special PVC compound TFF per le sezioni AWG18 (1 mmq) e AWG16 (1.5 mmq) TFF for section AWG18 (1 mmq) and AWG16 (1.5 mmq) THHW UL Listed dalla sezione AWG14 (2.5 mmq) THHW UL Listed cross to section AWG14 (2.5 mmq)



TENSIONE DI PROVA
TEST VOLTAGE

4000 V



COLORAZIONE CONDUTTORI
CORES COLORATION

Neri numerati con o senza g/v
Black numbered with or without y/g



TEMPERATURE DI ESERCIZIO
TEMPERATURES RANGE

Posa fissa/Fixed installation
- 40° C / + 90° C



SCHEMATURA
SHIELD

Treccia di rame stagnato, copertura 85%
Tinned copper braid, coverage 85%



RAGGIO DI CURVATURA
BENDING RADIUS

Posa fissa/Fixed installation
6 x ø



SEPARATORE
WRAPPING

Nastro di poliestere
Polyester tape



GUAINA ESTERNA
OUTER SHEATH

PVC speciale acc. UL 1277 e UL 1063 nero RAL 9005
Special PVC acc. to UL 1277 and UL 1063 black similar RAL 9005

NORMATIVE

NORMS



COMPORAMENTO AL FUOCO
FIRE PERFORMANCE

Acc. to UL 1581 FT4/IEEE 1202
Vertical-Tray Flame test



OIL RESISTANT
OIL RESISTANT

Acc. to UL OIL RES. I



UV RESISTANT
UV RESISTANT

ISO 4892-2



WATER RESISTANT
WATER RESISTANT

UL Wet Approval 75 °C

RIFERIMENTI STANDARD | STANDARD REFERENCE

Conforme a NFPA 79 2007 wiring norms e NEC 336.10 (7) Class 1, Div.2 secondo NEC art. 336,392,501 Conform to NFPA 79 2007 wiring norms and NEC 336.10 (7) Class 1, Div.2 acc. NEC art. 336,392,501 | UL Listed Acc. to UL 1277 Tray Cable - Exposed Run (TC-ER) and acc. to UL 1063 Machine Tool Wire (MTW) UL and CSA Recognized acc to UL Style 10012 and 2587 AWM I/II A/B Acc. to UL 2277 | Acc. to CSA 239-09

MARCATURA

MARKING

SADACAVI® SPA SADATRAY CY - formazione - lotto Made in Italy (UL) FILE E. / TC-ER OIL RESISTANT | DIR-BUR - formazione AWG 600V 90°C DRY/ 75°C WET FT4/ IEEE 1202 SUN RES o MTW " FLEXING" o AWM 2587 c(UL) CONTROL CABLE CIC -TC PVC FT4 o AWM I/II AB 90°C 600 V FT1 section AWG - mese - anno - metrica SADACAVI® SPA SADATRAY CY - size - lot Made in Italy (UL) FILE E. / TC-ER OIL RESISTANT | DIR-BUR - size AWG 600V 90°C DRY/ 75°C WET FT4/IEEE 1202 SUN RES or MTW " FLEXING" or AWM 2587 c(UL) CONTROL CABLE CIC -TC PVC FT4 or AWM I/II AB 90°C 600 V FT1 section AWG - month - year - metric marking

USO

USE

Cavi Multipolari schermati a norme UL/CSA di comando e controllo, per posa fissa, per alimentazione apparecchiature elettriche destinate al mercato Nord Americano. Possono essere utilizzati per applicazioni con sollecitazioni meccaniche medie dove è richiesta la libera circolazione senza sforzi di trazione e senza forzature sistemi di guida, in ambienti asciutti, umidi e bagnati (includere miscele di acqua e olio). UL MTW TC-ER (Cavo Exposed Run) secondo NEC 336,10 (7).

UL/CSA shielded command and control multicores cables, for fixed installation, mainly used for power supply of electrical equipment intended for North America market. Suitable for machine tools subjected to medium mechanical stresses, for flexible installation, where free movement is required without tensile stresses and without forced guidance systems, in dry, damp and wet interiors (including water-oil mixtures). UL MTW TC-ER (Cavo Exposed Run) acc. NEC 336,10 (7).

CAVI POSA FISSA OIL RESISTANT A NORME MTW TC-ER UL LISTED | OIL RESISTANT MTW TC-ER UL LISTED CABLES FIXED INSTALLATION

CODICE CODE	FORMAZIONE SIZE (MM)			AWG	DIAMETRO ESTERNO OVERALL DIAMETER (MM)	CU (KG/KM)	PESO WEIGHT (KG/KM)
TRAYCY2AWG18	2	x	1	18	8,5	44,0	99,6
TRAYCY3AWG18	3	G	1	18	8,9	58,5	120,4
TRAYCY4AWG18	4	G	1	18	9,7	67,9	142,9
TRAYCY5AWG18	5	G	1	18	10,5	82,6	172,0
TRAYCY7AWG18	7	G	1	18	11,4	106,8	210,2
TRAYCY8AWG18	8	G	1	18	13,9	121,2	276,0
TRAYCY12AWG18	12	G	1	18	15,5	185,3	348,5
TRAYCY18AWG18	18	G	1	18	17,9	260,7	483,4
TRAYCY25AWG18	25	G	1	18	20,3	336,5	605,8
TRAYCY2AWG16	2	x	1,5	16	9,2	58,5	122,3
TRAYCY3AWG16	3	G	1,5	16	9,7	72,7	144,5
TRAYCY4AWG16	4	G	1,5	16	10,5	92,2	181,9
TRAYCY5AWG16	5	G	1,5	16	11,4	111,6	215,9
TRAYCY7AWG16	7	G	1,5	16	12,4	145,3	267,0
TRAYCY8AWG16	8	G	1,5	16	15,4	185,5	370,0
TRAYCY12AWG16	12	G	1,5	16	16,9	251,8	446,9
TRAYCY18AWG16	18	G	1,5	16	19,6	355,6	626,1
TRAYCY25AWG16	25	G	1,5	16	23,4	474,0	767,1
TRAYCY2AWG14	2	X	2,5	14	10,0	82,5	155,6
TRAYCY3AWG14	3	G	2,5	14	10,5	106,6	188,3
TRAYCY4AWG14	4	G	2,5	14	11,4	135,6	239,5
TRAYCY5AWG14	5	G	2,5	14	12,5	164,4	285,7
TRAYCY7AWG14	7	G	2,5	14	14,6	229,6	385,6
TRAYCY12AWG14	12	G	2,5	14	18,5	375,9	605,3
TRAYCY18AWG14	18	G	2,5	14	22,6	537,5	847,0
TRAYCY3AWG12	3	G	4	12	11,9	154,6	256,0
TRAYCY4AWG12	4	G	4	12	13,0	198,1	329,8
TRAYCY5AWG12	5	G	4	12	15,2	262,1	433,8
TRAYCY7AWG12	7	G	4	12	16,5	348,0	545,1
TRAYCY3AWG10	3	G	6	10	13,9	217,2	354,1
TRAYCY4AWG10	4	G	6	10	15,3	300,7	474,6
TRAYCY5AWG10	5	G	6	10	16,7	367,0	568,5
TRAYCY4AWG8	4	G	10	8	19,4	480,8	766,0
TRAYCY5AWG8	5	G	10	8	22,4	585,4	956,7
TRAYCY4AWG6	4	G	16	6	24,6	737,3	1.201,0
TRAYCY5AWG6	5	G	16	6	27,1	899,7	1.444,8
TRAYCY4AWG4	4	G	25	4	28,1	1.100,6	1.693,7
TRAYCY5AWG4	5	G	25	4	31,1	1.357,9	2.058,7
TRAYCY4AWG2	4	G	35	2	31,0	1.502,0	2.202,3
TRAYCY4AWG1	4	G	50	1	37,7	2.166,7	3.204,4
TRAYCY4AWG2/0	4	G	70	2/0	44,2	2.976,1	4.397,1
TRAYCY4AWG3/0	4	G	95	3/0	47,7	3.963,5	5.565,9
TRAYCY4AWG4/0	4	G	120	4/0	50,3	4.937,2	6.652,3